Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A memory device comprising:

an interface which interfaces with an external device;

an IC chip which <u>comprises an EEPROM for storing a plurality of stores one</u> or more application programs and <u>a CPU for executing executes</u> said application programs;

a <u>nonvolatile</u> memory which stores associated data associated with said one or more application programs; and

a controller connected with said interface, said IC chip, and said <u>nonvolatile</u> memory;

wherein said IC chip, said nonvolatile memory and said controller are comprised of separate chips; and

wherein said controller, in response to a predetermined command received from said external device by way of said interface, performs transfer of said associated data between said IC chip and said <u>nonvolatile</u> memory without passing said associated data to <u>said a</u> host device during transfer of said associated data between said IC chip and said <u>nonvolatile</u> memory.

2. (Currently Amended) A memory device as recited in claim 1 wherein:

said nonvolatile memory is divided into a plurality of blocks; and

each of said plurality of blocks to be assigned to an application program to store said associated data associated with said assigned application program.

- 3. (Currently Amended) A memory device as recited in claim 2 wherein said nonvolatile memory includes a management area to store an association between an application ID used to identify each one of said application programs and an operation code used to transfer said associated data associated with said one application program between said nonvolatile memory and said IC chip through said controller.
- 4. (Currently Amended) A memory device as recited in claim 3 wherein said nonvolatile memory is controllable to operate in a locked mode to disable changing and adding and deleting an application ID in said nonvolatile memory associated with an application program stored in said IC chip when at least one application program is stored in said IC chip, and an unlocked mode to permit changing and adding and deleting an application ID in said nonvolatile memory.
- 5. (Currently Amended) A memory device as recited in claim 3 wherein said IC chip transfers an application ID in said IC chip, and wherein said controller compares said [[an]] application ID from said IC chip with an application ID from said nonvolatile memory, and, if there is a match between said application ID from said IC chip and said application ID from said nonvolatile memory, allows transfer of said associated data associated with said application program identified by said application ID between said IC chip and said nonvolatile memory.
- 6. (Original) A memory device as recited in claim 3 wherein said operation code is unique to said application ID associated with said operation code.
- 7. (Currently Amended) A memory device as recited in claim 1 wherein said associated data is already stored in said **nonvolatile** memory when said memory device is first used.
- 8. (Currently Amended) A memory device as recited in claim 1 wherein said controller which performs transfer of associated data associated with an application program between said IC chip and said **nonvolatile** memory, in response to said predetermined command,

by a transfer command associated with said application program sent from said **nonvolatile** memory to said IC chip.

9. (Currently Amended) A memory device comprising:

an IC chip which <u>comprises an EEPROM for storing a plurality of application</u>

programs and a CPU for executing executes one or more application programs;

a <u>nonvolatile</u> memory divided into a plurality of blocks, each block to be assigned to an application program executed by said IC chip; and

a controller controlling access to said <u>nonvolatile</u> memory and said IC chip; <u>wherein said IC chip</u>, said nonvolatile memory and said controller are <u>comprised of separate chips</u>;

wherein said <u>nonvolatile</u> memory stores one or more command codes used to allow said controller to query said IC chip regarding an instruction to perform an operation, said instruction being issued by said IC chip to said controller, each command code being associated with an application ID for identifying an application program;

wherein, in response to an application ID associated with an application program, said application ID <u>in IC chip</u> being sent <u>to said controller</u> by said IC chip <u>to said controller</u> for executing <u>which executes</u> said application program <u>of said application ID</u>, said controller identifies, out of said one or more command codes stored in said <u>nonvolatile</u> memory, a command code associated with said application ID from said IC chip, and sends said identified command code to said IC chip; and

wherein, in response to an instruction to perform an operation issued by said IC chip to said controller based on said identified command code, said controller performs said operation.

- 10. (Currently Amended) A memory device as recited in claim 9 wherein said command code includes a first transfer command for transferring data to be written to a block in said **nonvolatile** memory from said IC chip to said controller and a second transfer command for transferring data read from a block in said **nonvolatile** memory by said controller to said IC chip.
- 11. (Currently Amended) A memory device as recited in claim 10 wherein said IC chip sends the application ID to said controller <u>in response to an IC command</u> for executing said application program <u>based on a request</u> from the controller <u>in response to</u>, <u>wherein the IC command is extracted from</u> an external command received by the controller, and wherein the external command differs from the first transfer command and the second transfer command of the command code.
- 12. (Original) A memory device as recited in claim 10 wherein the instruction to perform an operation issued by said IC chip specifies which of the first transfer command and the second transfer command is to be performed.
 - 13. (Currently Amended) A memory device comprising:

an IC chip which <u>comprises an EEPROM for storing a plurality of application</u>

<u>programs and a CPU for executing executes one or more application programs;</u>

a <u>nonvolatile</u> memory divided into a plurality of blocks, each block to be assigned to an application program executed by said IC chip; and

a controller controlling access to said <u>nonvolatile</u> memory and said IC chip; wherein said IC chip, said nonvolatile memory and said controller are comprised of separate chips; and

wherein said controller, in response to a first command from an external device, assigns a usage privilege for a block in said <u>nonvolatile</u> memory to a particular application program to be executed by said IC chip; and, in response to a second command from the external device, changes from an unlocked state allowing execution of an operation in response to said

first command to a locked state disallowing execution of said operation in response to said first command.

14. (Currently Amended) A memory device as recited in claim 13 wherein:

said <u>nonvolatile</u> memory stores management information used to manage associations between identifiers for said blocks and identifiers for application programs for which usage privilege has been assigned for said blocks;

said controller allows contents of said management information to be changed in said unlocked state; and

said controller disallows contents of said management information to be changed in said locked state.

15. (Currently Amended) A memory device as recited in claim 13 wherein:

said <u>nonvolatile</u> memory stores management information used to manage associations between identifiers for said blocks and identifiers for application programs for which usage privilege has been assigned for said blocks; and

said controller, when said usage privilege for a block is assigned to an application program, adds an identifier for said application program associated with an identifier for said block to said management information.

16. (Currently Amended) A memory device as recited in claim 13 wherein:

said <u>nonvolatile</u> memory stores a flag for identifying whether execution of said operation in response to said first command is allowed or disallowed; and

said controller changes said flag when changing from said unlocked state to said locked state in response to said second command.

- 17. (Original) A memory device as recited in claim 13 wherein said controller changes from said locked state to said unlocked state in response to a third command from said external device.
 - 18. (Currently Amended) A memory device as recited in claim 17 wherein: said **nonvolatile** memory stores a reference password; and

said controller changes from said locked state to said unlocked state in response to said third command if a password received from said external device matches said reference password in said <u>nonvolatile</u> memory.

- 19. (Original) A memory device as recited in claim 13 wherein said controller disables usage privilege for a block assigned for an application program in response to a fourth command from said external device.
 - 20. (Currently Amended) A memory device as recited in claim 19 wherein:

said <u>nonvolatile</u> memory stores management information used to manage associations between identifiers for said blocks and identifiers for application programs for which usage privilege has been assigned for said blocks; and

said controller removes from said management information an identifier for said application program associated with an identifier for said block when disabling usage privilege for said block assigned for said application program.

- 21. (Currently Amended) A memory device as recited in claim 13 wherein said <u>nonvolatile</u> memory includes a first area for storing data received from said external device and a second area comprising said blocks for which usage privilege is assigned for said application programs.
- 22. (Currently Amended) A memory device as recited in claim 21 wherein said controller generates, for each application program, transfer command codes for identifying

transfer commands for receiving data <u>read from</u> to be written to said second area of said <u>nonvolatile</u> memory from said IC chip and for sending data to be written to said second area to said IC chip.

23. (Original) A memory device as recited in claim 22 wherein said transfer command codes are unique to each application program.

24.-27. (Canceled)

- 28. (Currently Amended) A memory device as recited in claim 9 [[25]] wherein said-data sent to said external device comprises said IC chip sends to said controller output data in an output data field including a first control byte, a second control byte, and trailing output according to format of the ISO 7816 specifications, and wherein both said application ID and said instruction to perform an operation from said IC chip is sent as said trailing data.
- 29. (Currently Amended) A memory device as recited in claim 28 wherein said output data sent to said external device further comprises at least one status word byte.
 - 30. (Canceled)
- 31. (Currently Amended) A memory device as recited in claim 24 wherein said interface memory includes nine terminals.
- 32. (New) A memory device as recited in claim 3, wherein said nonvolatile memory further includes a secure area and a normal area, wherein said secure area is divided into a plurality of blocks, wherein each block is assigned to each application program and stores associated data with each application program, and wherein said normal area stores data from said external device.
- 33. (New) A memory device as recited in claim 32 wherein said controller sends said operation code to said IC chip, to transfer to said IC chip said associated data which

was read from said secure area or to request from said IC chip said associated data which is to be written into said secure area.

34. (New) A memory device as recited in claim 3, wherein said controller individually generates said operation code for each application program when said controller assigns said block to said application program.